ELEV / HGT in FT MSL
unless otherwise stated

World Geodetic System - 1984 (WGS-84). WGS-84 Spheroid.
Lambert Conformal Conic projection.
Standard Parallels 54°40' and 57° 20' N.

NAVIAIR

Naviair
DENMARK

Compiled and published by Naviair
in corporation with Royal Danish Air Force.
Copyright © Landmäteriverket, Sweden
Agency for Data Supply and Efficiency, Denmark
Naviair, Denmark.
This chart is not an authority on territorial boundaries.
Printed by C. A. Backhausen Aps, Copenhagen.

AERONAUTICAL CHART - ICAO
ANC 1 : 500 000 DENMARK

EDITION 38

Publication Date: 17 Mar 2016
Effective Date: 31 Mar 2016

CONVERSION GRAPH
(1 meter = 3.28 feet)

Meters 1500 1400 1300 1200 1100 1000 900 800 700 600 500 400 300 200 100 0
Feet 4900 4800 4700 4600 4500 4400 4300 4200 4100 4000 3900 3800 3700 3600 3500 3400 3300 3200 3100 3000 2900 2800 2700 2600 2500 2400 2300 2200 2100 2000 1900 1800 1700 1600 1500 1400 1300 1200 1100 1000 900 800 700 600 500 400 300 200 100 0

ELEVATION TINTS

FEET
750
500
250
MSL

MORSE CODE

A	·–	N	–·
B	–···	O	–––
C	–·–·	P	·––·
D	–··	Q	––·–
E	·	R	·–·
F	··–·	S	···
G	––·	T	–
H	····	U	··–
I	··	V	···–
J	·–––	W	·––
K	–·–	X	–··–
L	·–··	Y	–·––
M	––	Z	––··

ISOGONIC LINES 2015

Annual rate of change:
W VAR -8' E VAR +8'

GLIDING

Gliding areas shown on:
ANC1 1:250 000 - COPENHAGEN AREA
Reporting sector limit

For additional information regarding VFR flights within København FIR - see reverse

LEGEND

BUILD-UP AREAS
- Town more than 2000 inhabitants
- Town below 2000 inhabitants
- Village

ROADS
- Dual highway
- Primary road
- Secondary road

RAILROADS
- Single track
- Multiple track

TOPOGRAPHY
Vertical Datum: DANISH MEAN SEA LEVEL
- Contour line (250 FT interval)
- .404 Spot elevation
- Woods

HYDROGRAPHY
- Tidal flat
- River / Stream / Canal
- Lake

MISCELLANECUS
- Ferry
- Windmill (height below 328 FT)
- International / Territorial boundary
- Isolated church
- Sea wall / Dike

- Major transmission line

MARITIME TRASIT ROUTES
- Maritime Transit Routes

ISOGONIC LINES 2015
- Annual rate of change: W VAR -8' E VAR +8'

AERODROMES
- Civil
- Joint Civil and Military
- Aerodrome with no facilities
- Direction of longest runway
- Runway pattern of the aerodrome may be shown in lieu of the aerodrome symbol
- Frequent glider activity on aerodrome
- Aeronautical ground light on aerodrome
- Name of aerodrome: AALBORG
- Elevation in FT–(-10), H 26.54 – (Length of longest runway (M x 100)
- Minimum lighting
- Runway surface Hard (H) or Grass (G)
- A dash (-) is inserted where L, H or G do not apply
- Frequent parashute activity on aerodrome
- Hang glider site
- Parachuting takes place frequently
- IFR cloudbreaking procedures take place by emergency medical services helicopters in uncontrolled airspace
- Heliport
- Glider site

RADIO FACILITIES
- NDB Non-Directional Radio Beacon
- TACAN Tactical Air Navigation System
- DME Distance Measuring Equipment
- VOR VHF Omnidirectional Radio Range
- VOR / TAC
- VOR /DME

ATS AIR SPACE
- Flight Information Region (FIR)
- Local ATS Area
- Control Zone (CTR)
- Traffic Information Zone (TIZ)
Radio Mandatory Zone (RMZ) (in Germany)
- Terminal Control Area / Traffic Information Area (TMA / TIA)
- Flight Information Service Sector (FIS)

Note ! A red color is used to emphasize CTR / TIZ

AIR NAVIGATION OBSTACLES
- Obstacle and group. Lighted
- Obstacle and group
- Obstacle with flare stack. Avoid overflying below 2.000 FT
- Exceptional high obstacle - Lighted and Unlighted. Height of 1000 ft above GND or more.
- Exceptional high obstacle - group in line. Lighted
- Wind turbine and group. Lighted
- Wind turbines - group in line. Lighted
- Wind turbines - group in major area. Lighted

VFR
- VFR Reporting point
- IFR REP on FIR BDRY
- VFR Route

PROHIBITED, RESTRICTED AND DANGER AREAS
- P Prohibited
- R Restricted
- D Danger Area
- 1000 GND — Area with sensitive fauna. Overflying such areas below 1.000 FT shall be avoided.

LIGHTS
- Aeronautical ground light
- Maritime light

Gp	Group
Fl	Flashing
LFl	Long Flashing
Occ	Occulting
Iso	Isophase
F	Fixed
Alt	Alternating
W	White

MAXIMUM ELEVATION FIGURES
The figures shown within each 30' quadrangle indicate either -
1. the highest terrain elevation plus 328 FT, *
2. the elevation of highest man-made obstacle – whichever is highest - increased to the nearest higher 100 FT level.

Example:
Terrain elevation 315 FT + 328 FT = 07
Obstacle elevation 932 FT = 10

GEOREF
LM — Geographical reference system

ADJACENT CHART SERIES
2151 | 2152 | 2170 | 2169
Numbers refer to charts in WAC - ICAO series

Consult AIP and NOTAM for latest information

No responsibility is taken for air data outside of Denmark.

Users noting errors or omissions on this chart are kindly requested to inform

Naviair
AIM-office
Naviair Alle 1
DK – 2770 Kastrup

TEL: +45 32 47 82 21
E-mail: aim@naviair.dk

ELEV / HGT in FT MSL
unless otherwise stated

KILOMETRES
STATUTE MILES
NAUTICAL MILES

KILOMETER
ENGELSKE ML
NØML