



NOTAS

- (1) No autorizados vuelos VFR.
- (2) O Hasta la elevación del techo de nubes, lo que resulte más bajo.
- En ningún caso se cruzará el eje de pista ni su prolongación sin autorización de APP o TWR.

LLEGADAS

Los pilotos establecerán contacto radio con APP como mínimo 5 minutos antes de alcanzar los puntos de notificación VFR. Se realizarán esperas sobre los puntos N (Montblanc), S (L'Hospitalet de L'Infant) y W (Falset) a una altitud de 3000 ft AMSL o sobre el punto E (Roda de Barà) a una altitud máxima de 2000 ft AMSL y solicitarán autorización a Reus APP para entrar en la CTR. Si procede, estarán autorizados desde el punto de espera VFR a integrarse, lo más directo posible, en el circuito de tránsito de aeródromo proporcionándoles instrucciones para el aterrizaje.

FALLO DE COMUNICACIONES

Las aeronaves con fallo de comunicaciones mantendrán 500 ft AGL o inferior.

OBSERVACIONES

- PAPI (MEHT) RWY 07: 3º (55 ft)
RWY 25: 3º (49 ft)
- A título informativo se incluyen las coordenadas geográficas de los puntos:
N: 412203N 0010955E
E: 411046N 0012750E
S: 410025N 0005515E
W: 410816N 0004920E

NOTES

- (1) VFR Flights not authorized.
- (2) Or up to the cloud ceiling, whichever is lower.
- Under no circumstances may the runway centerline or its extension be crossed without TWR or APP clearance.

ARRIVALS

Pilots shall establish radio contact with APP at least 5 minutes before reaching the VFR reporting points. Holdings shall be accomplished over the points N (Montblanc), S (L'Hospitalet de L'Infant) and W (Falset) at 3000 ft AMSL altitude, or over the point E (Roda de Barà) at 2000 ft AMSL maximum altitude, and clearance shall be requested from Reus APP to enter the CTR. If applicable, pilots will be cleared from the VFR points to join the aerodrome traffic circuit and provided with landing instructions.

COMMUNICATIONS FAILURE

Aircraft with communication failure shall maintain 500 ft AGL or below.

REMARKS

- PAPI (MEHT) RWY 07: 3º (55 ft)
RWY 25: 3º (49 ft)
- Purely for information, the geographic coordinates of the points are included:
N: 412203N 0010955E
E: 411046N 0012750E
S: 410025N 0005515E
W: 410816N 0004920E

CAMBIOS: FRECUENCIA APP/TWR, IDIOMA, SIMBOLOGÍA, //
CHANGES: APP/TWR FREQUENCY, LANGUAGE, SYMBOLS.

INTENCIONADAMENTE EN BLANCO
INTENTIONALLY BLANK